

TEMARED UNIVERSAL 5121/3 tilting with gangway three-axle GVW 3500kg



Product price:

5,476.28 €

Product short description:

Internal dimension (cm): **500 x 210**

Capacity: **2624 kg**

DMC Min: **2700 kg**

DMC Max: **3500 kg**

Product description:

A series of multi-purpose vehicle trailers with a tilting design, low overrun angle and a wide range of optional accessories. The transport surface can be tilted by means of a convenient hydraulic system. Loading, depending on the option chosen, by means of a split underrun, retractable under the transport surface or an aluminium or steel

underrun board. Can be equipped with 300 mm aluminium side boards and H1500 tarpaulin frame. Wheels R10C or R13C depending on version chosen. Welded, hot-dip galvanised frame, optionally equipped with a set of crossbars to further strengthen the frame. Transport surface made of non-slip waterproof plywood. Load capacity up to 2,750 kg. Maximum permissible GVW of 3.5 t.

Standard equipment

3 AL-KO axles, each 1250kg

Wheels: 195/55 R10

V-type drawbar

AL-KO overrun brake

Automatic support wheel

Welded steel frame

Total length 6.63 m

Transport surface: Waterproof, non-slip plywood

Corrosion protection: hot-dip galvanised

SPARE WHEEL AND SUPPORT BAR AVAILABLE AT EXTRA COST

Information:

Added specification on the website came from producers and distributors pages, despite the effort while we add them, they could have some mistakes. Descriptions and photos are not basis for claims from our company. If you found some mistakes in our description, please let us know to e-mail address sklep@mazzo.pl

